

**PRODUCT DESCRIPTION**

MIMI CUP 150 cc PS FULL COLOR BLACK

|                                |   |
|--------------------------------|---|
| 050201                         | Ø10,2 h5,3 cm Box of 300 pcs (6 bags of 50) (2 Times of 25) |
| <b>EAN Code:</b> 8027499003369 | <b>HS CODE:</b> 39269097                                    |
| <b>Type</b>                    | CUP   |
| <b>Color</b>                   | BLACK   |
| <b>Production Technique</b>    | Injection Molding   |



**PRODUCT DIMENSIONS**

|                        | External Dims. | (var.) | Internal Dims.         | (var.) | Bottom Dims. | (var.) |
|------------------------|----------------|--------|------------------------|--------|--------------|--------|
| <b>Lenght (cm)</b>     | -              | -      | -                      | -      | -            | -      |
| <b>Width (cm)</b>      | -              | -      | -                      | -      | -            | -      |
| <b>Diameter (cm)</b>   | 10,2 cm        | ± 5%   | -                      | -      | -            | -      |
| <b>Height (cm)</b>     | 5,3 cm         | ± 5%   |                        |        |              |        |
| <b>Useful Capacity</b> | 150 cc         | ± 5%   | <b>Capacity on top</b> |        | -            | -      |

**MATERIAL SPECIFICATIONS**

|                             |   |
|-----------------------------|---|
| <b>Type of Material</b>     | PS POLYSTYRENE FOOD GRADE TRANSPARENT OR COLOURED |
| <b>Material Composition</b> | -   |
| <b>Density (g/cm3)</b>      | 1,05 ± 5%   |

**PRODUCT SPECIFICATIONS**


|   |                         |                                  |
|---|-------------------------|----------------------------------|
| <b>Net Weight (g)</b>                         | 11,93 g                 | ± 5%                             |
| <b>Working load limit (Pa)</b>                | N/A                     |                                  |
| <b>Max temperature of use</b>                 | +70°C for 2 hours       |                                  |
| <b>Min temperature of use</b>                 | -18°C for over 6 months |                                  |
| <b>Suitable for food contact*</b>             | Suitable for all food   |                                  |
| <b>Repeated use for 125 washes up to 65°C</b> | YES                     |                                  |
| <b>Use in freezer (&lt;-18°C)</b>             | NO                      | <b>Use in blast chiller</b> NO   |
| <b>Use in convection oven</b>                 | NO                      | <b>Use in microwave</b> NO       |
| <b>Sterilization process</b>                  | NO                      | <b>Pasteurization process</b> NO |

\* In compliance with EU Regulations 10/2011, 1935/2004 and Italian laws. Declaration of conformity available on request.

**PACKAGING**


**BOX**

|                         |                             |
|-------------------------|-----------------------------|
| <b>Dimensions (cm)</b>  | L 27,5 x P 29,5 x H 34,5 cm |
| <b>Volume</b>           | 0,027988125 mc              |
| <b>Gross Weight Box</b> | 4,066 Kg                    |
| <b>Qty. per package</b> | 50 PCS                      |
| <b>Packages per box</b> | 6                           |
| <b>Total Qty.</b>       | 300 PCS                     |



**PALLET**

|                                 |   |
|---------------------------------|---|
| <b>Dimensions (cm)</b>          | L 80 x P 120 x H 216 cm - Configurazione PALLETEURO SC-GD406-50-20 (72) |
| <b>Pallet Volume</b>            | 2,0736 mc   |
| <b>Pallet Height (cm)</b>       | 216 cm  |
| <b>Pallet Gross Weight (kg)</b> | 312,752 kg  |
| <b>Boxes per Pallet</b>         | 72  |
| <b>Layers per Pallet</b>        | 6   |
| <b>Boxes per Layer</b>          | 12  |
| <b>Boxes on top</b>             | -   |
| <b>Qty. per Pallet</b>          | 21600 PCS   |



The information contained in this technical data sheet are indicative and subject to change without notice in order to improve functionality and design; the values provided are suggested as guidelines and should only be used to evaluate your specific application. In case of doubt, contact Polo Plast Srl. To the maximum extent permitted by law, Polo Plast Srl will not be liable for damages of any nature deriving from the improper use or reliance on the information contained in this technical data sheet. No express or implied warranties other than those required by law are provided.