

PRODUCT DESCRIPTION

EIS CUP 600 cc SMMA BLUE

060703	Ø16,8 h14 cm Box of 12 pcs (12 bags of 1)
EAN Code: 8027499029178	HS CODE: 39269097
Type	CUP
Color	BLUE
Production Technique	Injection Molding



PRODUCT DIMENSIONS

	External Dims.	(var.)	Internal Dims.	(var.)	Bottom Dims.	(var.)
Lenght (cm)	-	-	-	-	-	-
Width (cm)	-	-	-	-	-	-
Diameter (cm)	16,8 cm	± 5%	-	-	-	-
Height (cm)	14 cm	± 5%	-	-	-	-
Useful Capacity	600 cc	± 5%	Capacity on top		-	-

MATERIAL SPECIFICATIONS

Type of Material	SMMA Styrene methyl methacrylate
Material Composition	-
Density (g/cm3)	-

PRODUCT SPECIFICATIONS


Net Weight (g)	302 g	± 5%
Working load limit (Pa)	N/A	
Max temperature of use	+70°C for 2 hours	
Min temperature of use	-18°C for 1 month	
Suitable for food contact*	Suitable for all food	
Repeated use for 125 washes up to 65°C	YES	
Use in freezer (<-18°C)	NO	Use in blast chiller NO
Use in convection oven	NO	Use in microwave NO
Sterilization process	NO	Pasteurization process NO

* In compliance with EU Regulations 10/2011, 1935/2004 and Italian laws. Declaration of conformity available on request.

PACKAGING


BOX

Dimensions (cm)	L 40,4 x P 40,4 x H 37,9 cm
Volume	0,061858864 mc
Gross Weight Box	4,436 Kg
Qty. per package	1 PCS
Packages per box	12
Total Qty.	12 PCS



PALLET

Dimensions (cm)	L 80 x P 120 x H 236 cm - Configurazione PALLETEURO SC193 (36)
Pallet Volume	2,2656 mc
Pallet Height (cm)	236 cm
Pallet Gross Weight (kg)	179,696 kg
Boxes per Pallet	36
Layers per Pallet	6
Boxes per Layer	6
Boxes on top	-
Qty. per Pallet	432 PCS



The information contained in this technical data sheet are indicative and subject to change without notice in order to improve functionality and design; the values provided are suggested as guidelines and should only be used to evaluate your specific application. In case of doubt, contact Polo Plast Srl. To the maximum extent permitted by law, Polo Plast Srl will not be liable for damages of any nature deriving from the improper use or reliance on the information contained in this technical data sheet. No express or implied warranties other than those required by law are provided.